





1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 350nm—2.0 μ m
3. DIAMETER TOLERANCE: +0.0/−0.1 mm
4. THICKNESS TOLERANCE: ± 0.1 mm
5. FOCAL LENGTH: $f=20$ mm $\pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=17.3$ mm
7. CLEAR APERTURE: $>90\%$ CA
8. SURFACE QUALITY(S/D) (S1,S2) : 40/20
9. SURFACE FLATNESS (S1) : $\lambda/2$ @ 632.8 nm
10. SURFACE POWER (S2) : $3\lambda/2$ @ 632.8 nm
11. SURFACE IRREGULARITY (S2) : $\lambda/4$ @ 632.8 nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING (S1, S2) : UNCOATED

DRAWING PROJECTION 		
	NAME	DATE
DRAWN	JAC	18th/JUL./2025
APPROVAL	OLI	18th/JUL./2025
THE DRAWINGS ARE ONLY FOR TYPE SELECTION INFORMATION		

OLB-127-20

PLANO CONVEX LENS

Zolix

MATERIAL	WEIGHT	SCALE	REV
FOLLOW THE PARTS		5:1	1.0
shop.zolix.com.cn			