





1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 1100 nm–1650 nm
3. DIAMETER TOLERANCE: $+0.0/-0.1$ mm
4. THICKNESS TOLERANCE: ± 0.1 mm
5. FOCAL LENGTH: $f=25.4$ mm $\pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=17.6$ mm
7. CLEAR APERTURE: $>90\%$ CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2$ @ 632.8 nm
10. SURFACE POWER(S2): $3\lambda/2$ @ 632.8 nm
11. SURFACE IRREGULARITY(S2): $\lambda/4$ @ 632.8 nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING(S1,S2): AR COATING $R_{avg}<0.5\%$ @ 1100 nm–1650 nm

DRAWING PROJECTION						OLB-254-25-C							
			NAME			DATE			PLANO CONVEX LENS				
DRAWN			JAC			18th/JUL./2025							
APPROVAL			OLI			18th/JUL./2025							
THE DRAWINGS ARE ONLY FOR TYPE SELECTION INFORMATION													
						MATERIAL		WEIGHT		SCALE		REV	
						FOLLOW THE PARTS				5:1		1.0	
						shop.zolix.com.cn							