





1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 1100 nm–1650 nm
3. DIAMETER TOLERANCE: $+0.0/-0.1$ mm
4. THICKNESS TOLERANCE: ± 0.1 mm
5. FOCAL LENGTH: -50.0 mm $\pm 1\%$
6. BACK FOCAL LENGTH(REF): -52.1 mm
7. CLEAR APERTURE: $>90\%$ CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2$ @ 632.8 nm
10. SURFACE POWER(S2): $3\lambda/2$ @ 632.8 nm
11. SURFACE IRREGULARITY(S2): $\lambda/4$ @ 632.8 nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING(S1,S2): AR COATING $R_{avg} < 0.5\%$ @ 1100 nm–1650 nm

DRAWING PROJECTION						OLD-127-50-C		Zolix			
	NAME	DATE	PLANO CONCAVE LENS			MATERIAL	WEIGHT	SCALE	REV		
DRAWN	JAC	18th/JUL./2025				FOLLOW THE PARTS		5:1	1.0		
APPROVAL	OLI	18th/JUL./2025									
THE DRAWINGS ARE ONLY FOR TYPE SELECTION INFORMATION			shop.zolix.com.cn								