





1. DESIGN WAVELENGTH: 1016.0 nm, 1330.0 nm & 1550.0 nm
2. CLEAR APERTURE: >90%CA
3. OPERATION WAVELENGTH: 1100 nm–1650 nm
4. DIAMETER TOLERANCE: +0.0/–0.1 mm
5. THICKNESS TOLERANCE: ± 0.1 mm
6. FOCAL LENGTH: 400.0 mm $\pm 1\%$ @ 1330.0 nm
7. BACK FOCAL LENGTH(REF): 386.7 mm
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE POWER(S1,S2): $3\lambda/2$ @ 632.8 nm
10. SURFACE IRREGULARITY(S1,S2): $\lambda/4$ @ 632.8 nm
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1,S2): AR COATING $R_{avg} < 0.5\%$ @ 1100 nm–1650 nm

DRAWING PROJECTION						ZAC254-400-C				Zolix			
	NAME	DATE											
DRAWN	JAC	18th/JUL./2025	ACHROMATIC DOUBLET				MATERIAL	WEIGHT	SCALE	REV			
APPROVAL	OLI	18th/JUL./2025					FOLLOW THE PARTS		5:1	1.0			
THE DRAWINGS ARE ONLY FOR TYPE SELECTION INFORMATION							shop.zolix.com.cn						